




**PAWSAFE**

**COMMERCIAL FLOORING**



Flooring type	EN 13845	Safety Flooring
Slip classification	EN 13845	Class ESf-ESb
Abrasion resistance test	EN 13845	10% particles lost 50.000 Cycles
BS Pendulum test (Wet Test)	RRL	63 PTV
BS Pendulum test (Dry Test)	RRL	96 PTV
Surface Roughness test	Rz ≥ 20 µm	Low slip potential
Level of use	EN ISO 10874	34 - 43
Total thickness	EN ISO 24346	2.00 mm
Wear layer	EN ISO 24340	0.70 mm
Total weight/m2	EN ISO 23997	ca. 2.850 g
Heterogeneous PVC - PVC	ISO 10582	EN 13845
Width	EN ISO 24341	2000mm
Standard Length	EN ISO 24341	ca. 20m
Weight of standard roll		ca. 118-236 kg
Flammability	EN 13501	Bfl-S1
Residual indentation	EN ISO 24343	1 0,04 mm (norm ≤ 0,10 mm)
Furniture leg resistance	EN ISO 16581	Very good
Electrical resistance	EN ISO 10965	109
Ohm Static electrical propensity	EN 1815	≤ 2kV (antistatic)
Dimensional stability	EN ISO 23999	< 0.10%
Indoor Air quality		Low VOC
Light Fastness	ISO 105B02	6
Underfloor heating	EN 12524	Suitable
Cold Welding		Available
Warranty	Commercial	10 Years

The warranty covers manufacturing defects and premature wear in the event of normal use

